

SPEAKERCRAFT
a **Nice** brand

SC-DX-FC6-LCR

6½" In-Ceiling LCR Speaker



STAGE F SERIES

Feel the breath of the singer, the pick of the guitar, or the SFX of movies and games with crisp, room-filling sound

Versatile, Enhanced Performance

Featuring a 6 ½" injection molded polypropylene woofer angled down at 15 degrees and 1" aimable silk dome tweeter, the DX-FC6-LCR is ideal for music, movies, gaming and immersive sound applications where excellent performance and robust dynamics are required.



SC-DX-FC6-LCR

6½” In-Ceiling LCR Speaker (EACH)

Features

- **6 1/2” Injection Molded Polypropylene Angled Woofer**
Low crossover points and an angled woofer delivers the widest dispersion and best sound quality for LCR or distributed audio.
- **1” Pivoting Silk Dome Tweeter**
Silk dome tweeter delivers silky smooth highs which are pleasing to the ear.
- **Tilt Tweeter**
The aimable tweeter allows you to direct sound to the listening area, even when the speaker is mounted in less than ideal locations.
- **Low Profile Grill**
A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic—and with a one-step paint process, blends discreetly into any decor.
- **Easy-Grip Tweeter Bridge**
Installing speakers above your head requires a sturdy grip point and the SpeakerCraft Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.
- **Precision Tooled Diffusion Baffle**
Scattered concavities reduce reflection and disperse the sound evenly for a natural room filling experience.
- **Secure Connection**
All SpeakerCraft speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.
- **Timbre and Performance Matched**
Expect consistent dynamic and detailed sound in every Stage F series speaker.



Specifications

Woofer Size	6.5" (160mm)
Woofer Construction	Injection Molded Polypropylene Cone
Tweeter	1" (25mm) Pivoting Silk Dome
Frequency Response	51Hz-20kHz
Impedance	8 Ohms
Power Handling	110 Watts
Sensitivity	88 db
Timbre	Timbre-Matched to all F-Series Speakers
Dimensions	9.625" (237mm) Diameter 4.5" (114mm) Depth
Hole Cutout Dimensions	8.25" (210mm) Diameter
Depth Behind Wall	4.4" (111mm)

Use Pre-Construction Bracket
Model #: EL-PCB-IC-6



Niceforyou.com

©2023 Nice North America LLC. SpeakerCraft is a registered trademark of Nice North America LLC. All rights reserved.

Rev A - 06/2023

SPEAKERCRAFT
a Nice brand