SpeakerCraft Pro

After delivering literally millions of loudspeakers to the field, we are confident in our ability to provide performance and value that will impress even the most critical listener. We are now taking that same expertise and applying it to the commercial sector. We are fully aware of the unique requirements of the commercial contractor and have designed the SpeakerCraft Pro series to exceed those demands. The difference is our incredible attention to sound quality. We strongly believe that commercial installations benefit from increased sonic performance as much as any home theater or multi-room home audio system. With this philosophy we have crafted the SpeakerCraft Pro series to be the finest sounding commercial loudspeaker line on the market. If you have any doubts we welcome comparison. Listen for yourself. We know you will agree.

SC Pro Commercial 8

- 8" Polypropylene Cone Woofer
- 1" Pivoting Polyamide Dome Tweeter Mounted on a WavePlane™ Tweeter Baffle
- Efficiency: 88dB 1W/1m
- Power Handling: 5 - 100 Watts
- Transformer Taps (Com85-T): 70V: 64W, 32W,16W, 8W
- 100V: 64W, 32W, 16W + Transformer Bypass (8Ω)
- Impedance: 8 Ohms
- Frequency Response: 56Hz - 20kHz
- Diameter x Depth: 12 5/16" x 9 5/16" (329 mm x 236.47 mm)
- Cut-Out Diameter: 11½" (292.1 mm)
- Complete Polar Graph Available for Download Online

SC Pro Commercial 4

- 4" Polypropylene Cone Woofer
- ½" Pivoting Polyamide Dome Tweeter
- Efficiency: 85dB 1W/1m
- Power Handling: 5 - 80 Watts
- Transformer Taps (Com45-T): 70V: 32W,16W, 8W, 4W
- 100V: 32W, 16W, 8W + Transformer Bypass (8Ω)
- Impedance: 8 Ohms
- Frequency Response: 88Hz - 20kHz
- Diameter x Depth: 8 3/16" x 7 7/16" (207.97 mm x 192.1 mm)
- Cut-Out Diameter: 6¾" (171.45 mm)
- Complete Polar Graph Available for Download Online

SC Pro Commercial 6

- 6½" Polypropylene Cone Woofer
- 1" Pivoting Polyamide Dome Tweeter Mounted on a WavePlane™ Tweeter Baffle
- Efficiency: 88dB 1W/1m
- Power Handling: 5 - 140 Watts
- Transformer Taps (Com65-T): 70V: 64W, 32W,16W, 8W
- 100V: 64W, 32W, 16W + Transformer Bypass (8Ω)
- Impedance: 8 Ohms
- Frequency Response: 70Hz - 20kHz
- Diameter x Depth: 10 5/16" x 8 7/16" (261.87 mm x 214.12 mm)
- Cut-Out Diameter: 8⅞" (225.42 mm)
- Complete Polar Graph Available for Download Online

SC Pro Commercial Sub 8

- 8" Polypropylene Cone Woofer
- Available with Transformer
- Efficiency: 87dB 1W/1m
- Power Handling: 5 - 140 Watts
- Transformer Taps (Com Sub-T): 70V: 64W, 32W,16W, 8W
- 100V: 64W, 32W, 16W + Transformer Bypass (8Ω)
- Impedance: 8 Ohms
- Frequency Response: 30Hz - 200kHz
- Diameter x Depth: 12 15/16" x 13¾" (329 mm x 349 mm)
- Cut-Out Diameter: 11½" (292 mm)
- Complete Polar Graph Available for Download Online

* All SpeakerCraft Pro Commercial Speakers come with Limited LIFETIME Warranty
* As we incorporate design improvements, specifications may change without notice

All models are rated UL 1480

SpeakerCraft®

940 Columbia Ave., Riverside CA 92507 • USA (800) 448 0976 Fax (951) 787 8747 International +1 951 787 0543 • www.speakercraft.com