

## SC-DX-GC8 8" In-Ceiling Speakers

## **GRAND STAGE** SERIES

Experience the best seats in the house with the Grand Stage Series. Explosive dynamics, immersive soundstage, and nuanced realism.

### *HIGH PERFORMANCE* Clarity, Resolution & Dynamics

Featuring a graphite-injected polypropylene cone woofer and 1" aluminum dome tweeter with vocal contour and tweeter switches. Ideal for hi-fidelity music listening, home theater and media room applications where high performance is critical.

# SC-DX-GC8 8" In-Ceiling Speakers (PAIR)

### Features

#### 8" Carbon Composite Infused Polypropylene Woofer

Low Crossover points and a stiff, lightweight, and durable graphite injected cone woofer produces tight bass and transparent midrange for a crystal-clear, dynamic sound.

#### 1" Pivoting Aluminum Tweeter

Aluminum dome tweeters are lightweight, strong, and respond instantaneously to changes in music or movies.

#### Tilt Tweeter

The aimable tweeter allows you to direct sound to the listening area, even when the speaker is mounted in less than ideal locations.

Vocal and Tweeter Adjustment Switches
 Easily adjust tweeter performance or enhance
 the dialogue in movies.

#### Low Profile Grill

A thin-bezel magnetic grille ensures a secure fit, pleasing aesthetic—and with a one-step paint process, blends discreetly into any decor.

#### Easy-Grip Tweeter Bridge

Installing speakers above your head requires a sturdy grip point and the SpeakerCraft Tweeter bridge ensures you have one. We even protect the tweeter from accidental finger pokes.

#### Precision Tooled Diffusion Baffle

Scattered concavities reduce reflection and disperse the sound evenly for a natural room filling experience.

#### Secure Connection

Nice

All SpeakerCraft speakers feature spring loaded binding posts that provide a secure, worry-free connection in the wall or ceiling.

#### • Timbre and Performance Matched Expect consistent dynamic and detailed sound in every Grand Stage series speaker.



### Specifications

Woofer Size	8" (200mm)
Woofer Construction	Graphite Injected Polypropylene Cone
Tweeter	1" (25mm) Pivoting Aluminum Dome
Frequency Response	48Hz-20kHz
Impedance	8 Ohms
Power Handling	130 Watts
Sensitivity	90 db
Timbre	Timbre-Matched to all Grand Stage Series Speakers
Dimensions	10.8" (275mm) Diameter 4.65" (118mm) Depth
Hole Cutout Dimensions	9.75" (248mm) Diameter

Use Pre-Construction Bracket Model #: EL-PCB-IC-8





#### Niceforyou.com

©2023 Nice North America LLC. SpeakerCraft is a registered trademark of Nice North America LLC. All rights reserved. Rev A - 06/2023